

HIGH SPEED PRECISION LATHE

Bed Width: 190mm

SPECIFICATIONS	METRIC (INCH)		
Model NO.	KT-1324	KT-1340	KT-1440
Swing Over Bed	330mm (13")		360mm (14")
Swing Over Cross Slide	195mm (7-5/8")		225mm (8-3/4")
Swing Over Gap	490mm (19-1/4")		520mm (20-3/4")
Distance Between Centers	600mm (24")	1000mm (40")	
Bed Width	190mm (7-9/16")		
Number Of Spindle Speeds	9		
Range Of Spindle Speeds	82-2000R.P.M.		
Bore Through Spindle	40mm (1-1/2")		
Spindle Nose	D1-4 Camlock		
Taper Of Spindle Nose	MT 5		
Tailstock Quill Taper	MT 3		
Tailstock Quill Travel	100mm (4")		
Cross Slide Travel	165mm (6 1/2")		
Compound Rest Travel	100mm (4")		
Metric Threads	(30 Numbers) 0.4-7.0mm PITCH		
Inch Threads	(32 Numbers) 4-56TPI		
Longitudinal Feeds	12 Nos.(0.068-0.936mm/rev)/16 Nos.(0.0026-0.0638"/rev)		
Cross Feeds	12 Nos.(0.034-0.468mm/rev)/16 Nos.(0.0013-0.0319"/rev)		
Net Weight(kgs)	580	600	620
Gross Weight(kgs)	660	700	720
Packing Dimensions LxWxH	1473x762x1473mm(58"x30"x58")	1855x762x1473mm(73"x30"x58")	