

HIGH SPEED PRECISION LATHE

Bed Width: 260mm

SPECIFICATIONS	METRIC (INCH)	
Model NO.	KT-1640	KT-1660
Swing Over Bed	400mm (16")	
Swing Over Cross Slide	242mm (9-1/2")	
Swing Over Gap	552mm (21-3/4")	
Distance Between Centers	1000mm (40")	1500mm (60")
Bed Width	260mm (10")	
Number Of Spindle Speeds	12	
Range Of Spindle Speeds	50-2000R.P.M.	
Bore Through Spindle	55mm (2-3/16")	
Spindle Nose	D1-6 Camlock	
Taper Of Spindle Nose	MT 6	
Tailstock Quill Taper	MT 4	
Tailstock Quill Travel	110mm (4-3/8")	
Cross Slide Travel	200mm (8")	
Compound Rest Travel	90mm (3-9/16")	
Metric Threads	(32 Numbers) 0.4-7.0mm Pitch	
Inch Threads	(32 Numbers) 4-56TPI	
Module Threads	(32 Numbers) 0.4-7.0mm Mod.	
D.P. Threads	(32 Numbers) 8-120 D.P.	
Longitudinal Feeds	0.029-0.412mm/rev (0.0017" - 0.0242"/rev)	
Net Weight(kgs)	860	1020
Gross Weight(kgs)	960	1140
Packing Dimensions LxWxH	2083x864x1524mm (82"x34"x60")	2590x864x1524mm (102"x34"x60")