

CNC LATHE

SLANT BED TYPE



MODEL	KT-05	KT-06	KT-08
CAPACITY			
Swing over bed	300mm	480mm	560mm
Max cutting dia.	230mm	260mm	460mm
SPINDLE			
Spindle nose	A2-5	A2-6/A2-8(opt.)	A2-8
Spindle bore dia.	58mm	62mm/87mm-opt.	87mm/102mm-opt.
Spindle speed	6000rpm	4500rpm/3500rpm-opt.	3500rpm/3000rpm-opt.
Bar capacity	45mm(1.77")	52mm/75mm-opt.	75mm/90mm-opt.
Chuck size	6"	8"/10"(opt.)	10"/12"(opt.)
TRAVEL			
X axis	150mm(125+25mm)	175mm(150+25mm)	275(240+35mm)
Z axis	275mm	540mm	730mm/1230mm
FEEDS			
Rapid traverse-X axis	15m/min(590ipm)	15m/min(590ipm)	15m/min(590ipm)
Rapid traverse-Z axis	30m/min(1181ipm)	30m/min(1181ipm)	30m/min(1181ipm)
TURRET			
Type	Hydraulic	Hydraulic	Hydraulic
Number of tools	8	8/12	8/10/12
Tools shank	20mm	25mm	25mm
Boring bar size	25mm	32mm	40mm
TAILSTOCK			
Tailstock body travel	350mm	330mm	830mm/1330mm
Quill travel	60mm	75mm	100mm
Quill dia.	70mm	70mm	80mm
Quill taper	MT#4	MT#4	MT#5

• The above specifications subject to change without prior notice.

STANDRAD ACCESSORIES

- Hydraulic tailstock
- Automatic lubrication in linear guideways & ballscrews
- Cutting fluid coolant system
- Chip conveyor with cart
- Hydraulic turret
- Working light
- RS-232 port
- Hydraulic hollow chuck or collet chuck
- Warning light
- Levelling blocks
- Centers and center sleeve
- Service tools & toolbox
- Operation, programming & instruction manuals
- CE compliance

OPTIONAL ACCESSORIES

- Auto parts catcher
- Automatic door
- Auto tool probe
- Bar feeder
- Heavy duty rolling center
- Power transformer
- Power stabilizer
- Special functions by consult